



TANDBERG Tactical MXP

Portable and compact video communication tool for use in even the most remote and extreme conditions. Fully integrated and wireless system is ideal for off-site communication such as construction sites, manufacturing floors, defense operations and in-field media correspondence.

System delivered with shoulder strap and hand cart for unrivaled mobility



PROTECT YOUR TECHNOLOGY INVESTMENT. EXTEND THE LIFETIME OF YOUR PRODUCTS. TANDBERG's Constant Care Services fulfill customers' support needs from decision through deployment and beyond.

DESIGN FEATURES

- Designed for field use
- Fully integrated video system in a heavy-duty watertight case
- Meets most airline carry-on requirements
- Complete TANDBERG 3000 MXP core technology
- Hand cart included

APPLICATION FEATURES

- Join up to 4 video and 3 audio sites with embedded MultiSite functionality
- Best possible call for each MultiSite participant with rate matching and transcoding
- Powerful live presentations through one-step PC plug-in or LAN connection
- View presentations and presenter simultaneously with either DuoVideo or H.239 on single
- TANDBERG Expressway™ technology
- URI Dialing
- SIP
- Ability to integrate Type 1 encryption devices

PERFORMANCE FEATURES

- Up to 2 Mbps H.323 / 2 Mbps SIP / 512 kbps H.320 / 384 kbps V.35 / 2.3 Mbps total MultiSite
- Superior video quality incorporating the H.264 standard
- Highest level of standards-based embedded encryption (AES) is included
- True CD-quality audio
- Protection against network interruptions in point-to-point and multi-point calls with automatic Downsampling and IPLR
- PC card slot for wireless LAN connection
- Support for IP Quality of Service (QoS)

UNIT DELIVERED COMPLETE WITH:

Case with integrated 3000 MXP Codec, LCD Monitor, user interface, remote control, camera, microphone, speaker, shoulder strap, hand cart, AC to DC and DC-to-DC regulator, privacy audio headset.

MONITOR

Display Type: Color TFT LCD Screen
Screen Size: 15.4" Wide
Pixel Resolution: 1280x800 WXGA

BANDWIDTH

H.320 up to 512 kbps
H.323 up to 2 Mbps
SIP up to 2 Mbps

FIREWALL TRAVERSAL

TANDBERG Expressway Technology
Auto NAT

VIDEO STANDARDS

H.261, H.263, H.263+, H.263++ (Natural Video), H.264

VIDEO FEATURES

Native 16:9 Widescreen
Advanced Screen Layouts
Picture in Picture (PIP)
Picture outside Picture (POP)
Dual monitor emulation (Side by Side)
PC Zoom
Intelligent Video Management

VIDEO INPUTS (4 INPUTS)

Built-in main camera
1 x 9 Pin DSUB; S-video & control aux camera (Wave II)
1 x MiniDin, S-video; auxiliary / document camera
1 x RCA / Phono, composite; document camera / aux
1 x RCA / Phono, composite; VCR
1 x DVI-I/SXGA; PC
Input: 800 x 600 (@ 60, 72,75,85 Hz), 1024 x 768 (@ 60, 70, 75 Hz), 1280 x 1024 @ 60 Hz
Extended Display Identification Data (EDID)

VIDEO OUTPUTS (4 OUTPUTS)

1 x MiniDin, S-video; main monitor
1 x RCA / Phono, composite; main monitor or VCR
1 x RCA / Phono, composite; dual monitor or VCR
1 x DVI/XGA; main or second monitor
XGA OUTPUT
800 x 600 @ 75Hz, 1024 x 768 @ 60 Hz, 1280 x 768 (WXGA) @ 60 Hz
VESA Monitor Power Management

VIDEO FORMAT

NTSC, PAL, VGA, SVGA, XGA, W-XGA, or SXGA

LIVE VIDEO RESOLUTION

NATIVE NTSC:

4SIF (704 x 480 pixels), Digital Clarity
Interlaced SIF (352 x 480 pixels), Natural Video
SIF (352 x 240 pixels)

NATIVE PAL:

4CIF (704 x 576 pixels), Digital Clarity
Interlaced CIF (352 x 576 pixels), Natural Video
CIF (352 x 288 pixels)
QCIF (176 x 144 pixels)
SQCIF (128 x 96 pixels) decode only

NATIVE PC RESOLUTION:

XGA (1024 x 768)
SVGA (800 x 600 pixels)
VGA (640 x 480 pixels)

STILL IMAGE TRANSFER

CIF, SIF, 4CIF (H.261 Annex D), 4SIF, VGA, SVGA, XGA

AUDIO STANDARDS

G.711, G.722, G.722.1, G.728, 64 bit & 128 bit MPEG4 AAC-LD

AUDIO FEATURES

CD-Quality 20KHz Mono and Stereo
Telephone add-on via MultiSite
Two separate acoustic echo cancellers
Audio mixer
Automatic Gain Control (AGC)
Automatic Noise Reduction
Audio level meters
VCR ducking
Auto-switching for headset at connection

AUDIO INPUTS (5 INPUTS)

2 x microphone, 24V phantom powered, XLR connector
1 x RCA / Phono, Line Level: auxiliary (or VCR Stereo L)
1 x RCA / Phono, Line Level: VCR/DVD (Stereo R)
1 x Mini-jack 3.5 mm

AUDIO OUTPUTS (3 OUTPUTS)

1 x RCA / Phono, S/PDIF (mono/stereo) or Analogue Line Level: main audio
1 x RCA / Phono, Line Level: VCR
1 x Mini-jack 3.5 mm

FRAME RATES

30 frames per second @ 168 kbps and above
60 fields per second @ 336 kbps and above (Point-to-point)

DUAL STREAM

Duo Video & H.239
Available on H.323 & H.320
Available in Multisite from any site

NETWORK FEATURES

Auto H.320 / H.323 dialing
SIP
Downspeeding
Programmable network profiles
Intelligent Call Management
Maximum call length timer
Automatic SPID and line number configuration (National ISDN, GR-2941-CORE)
SoftMux
H.331 Broadcast Mode
NATO standard KG194 / KIV-7 encryptor support**
URI Dialing

MULTISITE FEATURES

H.323/H.320/SIP/Telephony/VoIP in the same conference
Audio and Video Transcoding
Video rate matching from 56 kbps - maximum conference rate
CP4 and Voice Switched
Best Impression (Automatic CP Layouts)
H.264, Encryption, Digital Clarity
Dual Stream from any site
ISDN & IP Downspeeding and IPLR
MultiSite (H.243) Cascading on H.320 & H.323
Dial in / Dial out
Chair control for host system
Snapshot of ongoing conference (JPEG)
Snapshot of ongoing DuoVideo/H.239 presentation (JPEG)
Separate welcome page for encrypted conferences
Conference rates up to 2.3 Mbps with optional bandwidth upgrade (1.5 Mbps is standard conference rate)
Up to 4 video and 3 audio sites
4 sites @ 768 kbps (+telephone calls)
Mix ISDN-BRI/V.35** and IP up to maximum conference rate

EMBEDDED ENCRYPTION

H.320 and H.323 point-to-point and multipoint calls
Standards-based: H.233, H.234, H.235 v2&v3, DES and AES
NIST-validated AES
NIST-validated DES
Automatic key generation and exchange
Supported in Dual Stream & MultiSite

IP NETWORK FEATURES

Differentiated Services (DiffServ)
Resource Reservation Protocol (RSVP)
IP precedence
IP type of service (ToS)
IP adaptive bandwidth management (including flow control)
Auto gatekeeper discovery
Dynamic playout and lip-sync buffering
Intelligent Packet Loss Recovery (IPLR)
H.245 DTMF tones in H.323
Cisco CallManager integration using ECS
IP Address Conflict Warning

SECURITY FEATURES

Management via HTTPS
IP Administration Password
Menu Administration Password
Dialing Access code
Streaming password
H243 MCU Password
VNC password
SNMP security alerts
Disable IP services
MD-5 Challenge
Network Settings protection
SIP Authentication via NTLM

NETWORK INTERFACES

4 x ISDN BRI (RJ-45), S-interface
1 x LAN/Ethernet (RJ-45) 10/100 Mbit (LAN/DSL/cable modem)
1 x PC card slot (PCMCIA) for wireless LAN
1 x X.21 / V.35 / RS-449 with RS-366 dialing, Leased Line**
1 x USB

WIRELESS LAN SUPPORT

Compliant with IEEE 802.11b, up to 11 Mbit
Support for 64 / 128 bit encryption (WEP)
Infrastructure or ad-hoc mode

ETHERNET / INTERNET / INTRANET CONNECTIVITY

TCP / IP, DHCP, ARP, FTP, Telnet, HTTP, HTTPS,
SOAP and XML, MD-5 Challenge
SNMP Enterprise Management
Internal web server
Internal streaming server

OTHER MAJOR STANDARDS SUPPORTED

H.231, H.233, H.234, H.235, H.235 v2&v3, H.239, H.241,
H.243, H.281, BONDING (ISO 13871), H.320, H.323, H.331
RFC 3261, RFC 2237, RFC 3264, RC 3311, RFC 3550,
RFC 2032, RFC 2190, RFC 2429, RFC 3407

CAMERA

1/4" CCD Color DSP Camera
752 (H) x 582 (V) Pixels
Min. illumination 1.2 Lux (Output level 50%/AGC On/F1.4)
+30 / -15 tilt

W.A.V.E. (WIDE ANGLE VIEW) II CAMERA (OPTIONAL)

10 x zoom 1/4" CCD +15° / -20° tilt + / -95° pan
61° vertical field of view
96° total vertical field of view
77° horizontal field of view
267° total horizontal field of view
460 (PAL) / 470 (NTSC) TV lines
Min. illumination 2 Lux (F1.8)
Auto or manual focus / brightness / white balance
Far-end camera control
15 near and far-end camera pre-sets
Voice-activated camera positioning
Daisy chain support for up to 4 cameras

CLOSED CAPTIONING/TEXT CHAT

T.140 text chat available from RS-232, Telnet,
Web and User Interface

PRESENTATIONS AND COLLABORATION

Natural Presenter Package including:
PC Presenter (DVI-I, SXGA In)
PC SoftPresenter
Digital Clarity & Native Formats
Advanced Video Layouts
Streaming compatible with Cisco IP/TV,
Apple QuickTime®, RealPlayer® v8 etc.

SYSTEM MANAGEMENT

Support for the TANDBERG Management Suite
Total management via embedded web server, SNMP,
Telnet, FTP and SOAP
Remote software upload: via web server or FTP server
1 x RS-232 local control and diagnostics
Remote control and on-screen menu system

DIRECTORY SERVICES

Support for Local, Global and Dynamic Server Directories
Unlimited entries using Server directory* supporting
LDAP and H.350
400 number global directory
200 number local directory
16 dedicated MultiSite entries
Last Number Called
Call History
Directories in Local Languages

13 SELECTABLE MENU LANGUAGES

Simplified Chinese, Traditional Chinese English,
French, German, Italian, Japanese, Korean, Norwegian,
Portuguese, Russian, Spanish and Swedish

CUSTOMIZED WELCOME SCREEN AND COMPANY LOGO

POWER

100 - 250 VAC, 50 - 60 Hz 60 watts max. LPS
12-32 V DC, 60 watts LPS

OPERATING TEMPERATURE AND HUMIDITY

0° C to 35° C (32° F to 95° F) ambient temperature
10% to 90% Relative Humidity (RH)

STORAGE AND TRANSPORT TEMPERATURE

-20° C to 60° C (-4° F to 140° F) at RH 10-90%
(non-condensing)

DIMENSIONS

Length: 21.2" / 54 cm
Height: 8.3" / 21 cm
Depth: 16" / 40 cm
Weight: 25.4 lbs / 11.5 kg

*** Optional equipment, must be specified at the time of order, Serial Port replaces ISDN BRI.*

** Requires TANDBERG Management Suite 9 or newer.*

System features vary depending on network selection and software package. All specifications subject to change without notice.

All photographs and images contained in these materials are for general, representational purposes only. Actual products may differ based upon component availability.

TANDBERG is a registered trademark or trademark of TANDBERG in the U.S. and other countries.

Cisco, Cisco Systems, the Cisco Systems logo, and the Cisco Arrow logo are registered trademarks or trademarks of Cisco Systems, Inc. and/or its affiliates in the U.S. and certain other countries.

RealPlayer is a trademark or a registered trademark of RealNetworks, Inc.

QuickTime is a registered trademark of Apple Computer, Inc., registered in the U.S. and other countries.

All other trademarks are property of their respective owners.

Contains iType™ from Agfa Monotype Corporation.

TANDBERG

Tactical MXP

TANDBERG WORLD HEADQUARTERS
Philip Pedersens vei 22
1366 Lysaker, Norway
Tel: +47 67 125 125
Fax: +47 67 125 234
Video: +47 67 117 777
E-mail: tandberg@tandberg.net

200 Park Avenue, Suite 2005
New York, NY U.S.A. 10166
Tel: +1 212 692 6500
Tel: +1 800 538 2884 (toll free in the U.S.)
Fax: +1 212 692 6501
Video: +1 212 692 6535
E-mail: tandberg@tandbergusa.com

April 2005